

Thermal Transfer Ribbons

TECHNICAL DATA SHEET



LABELS DIRECT

TR3022 Blue General Purpose Wax

PRODUCT DESCRIPTION

Based on our proven wax technology, these quality ribbons expand your color possibilities while providing excellent print clarity and high smudge resistance when black just isn't enough. These ribbons are also specially formulated with backcoat technology for printhead protection.

RECOMMENDED SUBSTRATES

Coated/uncoated paper & tag stocks, synthetic paper, polyethylene, polypropylene, top-coated vinyl, polyolefin, Tyvek®, Tyvek Brillion®

PERFORMANCE CHARACTERISTICS

- Provides excellent print clarity and is highly smudge resistant
- Prints at high speeds (12 IPS) delivering crisp, rotated bar codes
- Features a SmoothCoat® backcoat
- Unbeatable edge definition for dark, dense images and improved scan rates

RECOMMENDED APPLICATIONS



COLOR



GENERAL



HORTICULTURE



INVENTORY



OUTDOOR



PARTS
PACKAGING



PRODUCT ID



RETAIL



SHELF



SIGNAGE



TR3022 Blue
PMS 286C

Colors may vary by substrate
PMS = Pantone® Matching System

TR3022 Blue General Purpose Wax

RIBBON PROPERTIES

DESCRIPTION	RESULT	TEST METHOD
Ink	Wax	
Color	Blue	Visual
Total Thickness	$8.4 \pm 0.5\mu$	Micrometer
Base Film Thickness	$4.8 \pm 0.3\mu$	Micrometer
Ink Thickness	$3.6 \pm 0.2\mu$	Micrometer
Ink Melting Point	72°C (162°F)	Differential Scanning Calorimeter

DURABILITY OF PRINTED IMAGE

Label Stock: Coated Paper

Print Speed: 6 IPS

DESCRIPTION	RESULT	TEST METHOD
Print Density - Blue	Y: 0.08 - 0.56 M: 0.85 - 1.57 C: 1.18 - 1.94	Densitometer

CONVERSION CHART

Millimeters (mm) to Inches = $\text{mm} \div 25.4$

Meters (m) to Feet (ft) = $\text{m} \div 0.3048$

C° to F° = $(1.8 \times \text{C}^\circ) + 32 = \text{F}^\circ$

Thousand square inches (MSI) to m² = $\text{MSI} \times 0.645$

Inches to Millimeters (mm) = $\text{Inches} \div 0.03937$

Feet (ft) to Meters (m) = $\text{Feet} \div 3.2808$

F° to C° = $(\text{F}^\circ \div 1.8) - 17.77$

MSI = $\text{m}^2 \div 0.645$

Labels Direct, Inc.

664 Trade Center Blvd.

Chesterfield, MO 63005

Phone Support: 636-458-5156

Toll Free Support: 800-458-5110

Fax: 636-458-5693

The information on this data sheet was obtained in our laboratories. Measured values may vary slightly when tested in a different environment. Information contained within this document is subject to change without notification.

Visit us at
www.labelsdirect.com



LABELS DIRECT