

TR4055®

Standard Wax



Product Description

This wax product features a blend of waxes and a unique resin that are combined in an ink that flows smoothly at low print energy to give uniform coverage on lower end substrates. It also incorporates technology designed to control and dissipate static charges and a backcoat proven to protect your printhead. Specially formulated to provide excellent performance in a broad range of applications, this wax sets the standard for everyday thermal transfer printing.

Recommended Applications



Compliance



Inventory &
Logistics



Retail

Product Features

Halogen-free



High-density



High-speed



Made in U.S.A.



Scratch Resistant



Smudge Resistant



DNP

dnppribbons.com



DNP Global Locations

Americas China
Europe Japan
Singapore

DNP Imagingcomm America
Corporation
1001 Technology Drive
Mount Pleasant, PA 15666

TEL: +1 888.569.7222
FAX: +1 800.676.7669
EMAIL:
info@dnppimgcomm.com

TR4055®

Standard Wax

Product Specifications

Wax

Half Inch
TR3021 Red
TR3022 Blue
TR3023 Green
TR4055® Standard
TR4085plus® Premium Resin-Enhanced

Wax/Resin

M260 Ultra Durable
TRX-50 General Purpose
TRX-55 Premium

Resin

R300 General Purpose
R316 Specialty
R350 Permanent Care
R510C Durable Color
R510HF Ultra Durable
R510W Durable White
TR3370 High Opacity White
TR4070 Classic
VR301 Durable Metallic Color

Near Edge

M295 Plus Specialty Wax/Resin
M295C Specialty Wax/Resin Color
R390 Resin
R396 High Speed Durable Resin
TR4500 Premium Wax/Resin

Recommended Substrates

Paper

Coated Paper
Coated Tag
Uncoated Paper
Uncoated Tag

Ribbon Properties

Ink	Wax
Color	Black
Base Film Thickness	4.8 ± 0.3µ
Ink Thickness	3.0 ± 0.2µ
Total Thickness	7.8 ± 0.5µ
Ink Transfer Temperature	Uncoated Tag 67°C (152°F)



DNP

dnpribbons.com



DNP Global Locations

Americas China
Europe Japan
Singapore

DNP Imagingcomm America
Corporation
1001 Technology Drive
Mount Pleasant, PA 15666

TEL: +1 888.569.7222
FAX: +1 800.676.7669
EMAIL:
info@dnpribbons.com